

# G2500

## Adding flexibility to your business

Genmega introduces the **G2500** series ATM. Designed for retail and off-premise locations, the **G2500** comes loaded with all the features you expect, and also provides additional hardware configuration choices allowing you to custom fit each machine to the needs of your customer or location.

The **G2500** comes standard with an 8" high-resolution wide-screen LCD, which can be upgraded to a 10.2" touch-screen. The receipt printer can also be upgraded to a 3" graphics-capable for custom branding or coupons. The integrated topper can also be paired with a selection of energy-efficient LED toppers to add visual impact and attract customers.

In addition to the fixed, removable and multi cash cassette dispenser options offered by Genmega, the **G2500** can also support cash dispensers from other equipment suppliers, providing more flexibility and upgrade options for existing deployments.



# G2500

## Topper

Optional LED Topper Sign  
Can accept custom inserts

## Integrated Illuminated Sign

High Visibility LED Sign  
Attract Customers

## LCD Screen

8 inch diagonal 32-bit color  
Backlit TFT LCD panel  
800 x 480 Resolution  
10.2" touch-screen Optional  
Customizable Ad Screens

## Printer

56mm (2" standard)  
80mm (3" optional)  
Graphics Capable with 3"

## PIN Entry Device

16-key alphanumeric keypad  
PCI / Interac Certified  
Triple-DES (TDES) EPP

## Communication

56Kb Internal modem  
TCP/IP Ethernet - SSL



## CPU

Samsung 32-bit CPU  
64MB RAM / WinCE™ 5.0 OS  
Electronic Journal > 40K transactions

## Card Reader

DIP Style Magnetic Card Reader  
EMV Optional

## ADA

Voice Guidance  
Lighted Transaction Guidance  
Accessible Keypad Layout

## Security

UL291 Business Hours Vault  
Dial or Electronic Lock

## Cash Dispenser

800 Note Fixed Cassette (TCDU)  
1000 Note Removable Cassette (SCDU)  
1700 Note Removable Cassette (MCDU)  
2x1700 Note Multi-Cassette (MCDU)

## Dimensions

Height = 56.3"  
Width = 15.8"  
Depth = 22.3"  
Weight = 206 lbs

## Power Requirements:

110/220 VAC ± 10%, 50/60 Hz, 86 Watts

www.genmega.com